

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: February 05, 2018

Revision: February 05, 2018

1 Identification

- **Product identifier**
- **Trade name:** SOLVENT BASE DUCT SEALER - LOW VOC
- **Product code:** #5142 (SGDCLVOC)
- **Recommended use and restriction on use**
- **Recommended use:** Adhesives
- **Restrictions on use:** For professional use only.
- **Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**
DURO DYNE CORPORATION
81 Spence Street
Bay Shore, NY 11706
800-899-3876
- **Emergency telephone number:**
ChemTel Inc.
(800)255-3924 (North America)
+1 (813)248-0585 (International)

2 Hazard(s) identification

- **Classification of the substance or mixture**
Flam. Liq. 2 H225 Highly flammable liquid and vapor.
Eye Irrit. 2A H319 Causes serious eye irritation.
Repr. 2 H361 Suspected of damaging fertility or the unborn child. Route of exposure: Inhalation.
STOT SE 3 H336 May cause drowsiness or dizziness.
STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms:**



GHS02 GHS07 GHS08

- **Signal word:** Danger

- **Hazard statements:**

H225 Highly flammable liquid and vapor.
H319 Causes serious eye irritation.
H361 Suspected of damaging fertility or the unborn child. Route of exposure: Inhalation.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.

- **Precautionary statements:**

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.

(Cont'd. on page 2)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: February 05, 2018

Revision: February 05, 2018

Trade name: SOLVENT BASE DUCT SEALER - LOW VOC

(Cont'd. of page 1)

- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P260 Do not breathe mist/vapors/spray.
- P264 Wash thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/protective clothing/eye protection.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P370+P378 In case of fire: Use foam, powder, or carbon dioxide for extinction.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Other hazards** There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Components:**

79-20-9	methyl acetate ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2A, H319; STOT SE 3, H336	20-40%
67-64-1	acetone ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2A, H319; STOT SE 3, H336	10-20%
1317-65-3	limestone	<10%
108-88-3	toluene ⚠ Flam. Liq. 2, H225 ⚠ Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304 ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	<10%
1332-58-7	Kaolin	<10%
119-47-1	6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol ⚠ Repr. 2, H361	<1%
13463-67-7	titanium dioxide	<1%

· **Additional information:**

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret.
 For the wording of the listed Hazard Statements, refer to section 16.

4 First-aid measures

(Cont'd. on page 3)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: February 05, 2018

Revision: February 05, 2018

Trade name: SOLVENT BASE DUCT SEALER - LOW VOC

(Cont'd. of page 2)

Description of first aid measures**After inhalation:**

Supply fresh air; consult doctor in case of complaints.
Provide oxygen treatment if affected person has difficulty breathing.
In case of irregular breathing or respiratory arrest provide artificial respiration.
In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Immediately remove any clothing soiled by the product.
Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.

After eye contact:

Remove contact lenses if worn.
Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water.
Do not induce vomiting; immediately call for medical help.

Most important symptoms and effects, both acute and delayed:

Headache
Dizziness
Gastric or intestinal disorders
Nausea
Causes eye irritation.

Danger:

Danger of disturbed cardiac rhythm.
Danger of convulsion.
Danger of impaired breathing.

Indication of any immediate medical attention and special treatment needed:

In cases of irritation to the lungs, initial treatment with cortical steroid inhalants.
If necessary oxygen respiration treatment.
Medical supervision for at least 48 hours.

5 Fire-fighting measures**Extinguishing media****Suitable extinguishing agents:**

Water fog / haze
Foam
Alcohol resistant foam
Fire-extinguishing powder
Carbon dioxide

For safety reasons unsuitable extinguishing agents:

Water stream.
Water spray

Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

Advice for firefighters**Protective equipment:**

Wear self-contained respiratory protective device.
Wear fully protective suit.

(Cont'd. on page 4)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: February 05, 2018

Revision: February 05, 2018

Trade name: SOLVENT BASE DUCT SEALER - LOW VOC

(Cont'd. of page 3)

Additional information:

- Eliminate all ignition sources if safe to do so.
- Use large quantities of foam as it is partially destroyed by the product.
- Cool endangered containers with water fog.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

- Use respiratory protective device against the effects of fumes/dust/aerosol.
- Wear protective equipment. Keep unprotected persons away.
- Ensure adequate ventilation.
- Keep away from ignition sources.
- Protect from heat.

Environmental precautions Avoid release to the environment.**Methods and material for containment and cleaning up**

- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- Send for recovery or disposal in suitable receptacles.

Reference to other sections

- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

7 Handling and storage

Handling**Precautions for safe handling:**

- Ensure good ventilation/exhaustion at the workplace.
- Keep away from heat and direct sunlight.
- Keep out of reach of children.
- Avoid contact with the eyes and skin.

Information about protection against explosions and fires:

- Keep ignition sources away - Do not smoke.
- Use explosion-proof apparatus / fittings and spark-proof tools.
- Fumes can combine with air to form an explosive mixture.
- Flammable gas-air mixtures may be formed in empty containers/receptacles.
- Protect against electrostatic charges.
- The product forms flammable fumes when heated.

Conditions for safe storage, including any incompatibilities**Requirements to be met by storerooms and receptacles:**

- Avoid storage near extreme heat, ignition sources or open flame.
- Store in cool, dry conditions in well sealed receptacles.

Information about storage in one common storage facility:

- Store away from foodstuffs.
- Store away from oxidizing agents.

Further information about storage conditions:

- Protect from heat and direct sunlight.
- Protect from exposure to the light.

(Cont'd. on page 5)



Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: February 05, 2018

Revision: February 05, 2018

Trade name: SOLVENT BASE DUCT SEALER - LOW VOC

(Cont'd. of page 4)

Store receptacle in a well ventilated area.

· **Specific end use(s)** No relevant information available.

8 Exposure controls/personal protection

· Control parameters

· Components with limit values that require monitoring at the workplace:

79-20-9 methyl acetate

PEL (USA)	Long-term value: 610 mg/m ³ , 200 ppm
REL (USA)	Short-term value: 760 mg/m ³ , 250 ppm Long-term value: 610 mg/m ³ , 200 ppm
TLV (USA)	Short-term value: 757 mg/m ³ , 250 ppm Long-term value: 606 mg/m ³ , 200 ppm
EL (Canada)	Short-term value: 250 ppm Long-term value: 200 ppm
EV (Canada)	Short-term value: 755 mg/m ³ , 250 ppm Long-term value: 605 mg/m ³ , 200 ppm
LMPE (Mexico)	Short-term value: 250 ppm Long-term value: 200 ppm

67-64-1 acetone

PEL (USA)	Long-term value: 2400 mg/m ³ , 1000 ppm
REL (USA)	Long-term value: 590 mg/m ³ , 250 ppm
TLV (USA)	Short-term value: 1187 mg/m ³ , 500 ppm Long-term value: 594 mg/m ³ , 250 ppm BEI
EL (Canada)	Short-term value: 500 ppm Long-term value: 250 ppm
EV (Canada)	Short-term value: 750 ppm Long-term value: 500 ppm
LMPE (Mexico)	Short-term value: 750 ppm Long-term value: 500 ppm A4, IBE

108-88-3 toluene

PEL (USA)	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL (USA)	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm
TLV (USA)	Long-term value: 75 mg/m ³ , 20 ppm BEI
EL (Canada)	Long-term value: 20 ppm R
EV (Canada)	Long-term value: 20 ppm
LMPE (Mexico)	Long-term value: 20 ppm

(Cont'd. on page 6)



Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: February 05, 2018

Revision: February 05, 2018

Trade name: SOLVENT BASE DUCT SEALER - LOW VOC

(Cont'd. of page 5)

	A4, IBE
1332-58-7 Kaolin	
PEL (USA)	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV (USA)	Long-term value: 2* mg/m ³ E; as respirable fraction
EL (Canada)	Long-term value: 2 mg/m ³
EV (Canada)	Long-term value: 2(D) mg/m ³ respirable
LMPE (Mexico)	Long-term value: 2* mg/m ³ A4, *fracción respirable

13463-67-7 titanium dioxide	
PEL (USA)	Long-term value: 15* mg/m ³ *total dust
REL (USA)	See Pocket Guide App. A
TLV (USA)	Long-term value: 10 mg/m ³ withdrawn from NIC
EL (Canada)	Long-term value: 10* 3** mg/m ³ *total dust,**respirable fraction; IARC 2B
EV (Canada)	Long-term value: 10 mg/m ³ total dust
LMPE (Mexico)	Long-term value: 10 mg/m ³ A4

1317-65-3 limestone	
PEL (USA)	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV (USA)	TLV withdrawn

Ingredients with biological limit values:

67-64-1 acetone	
BEI (USA)	50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)

108-88-3 toluene	
BEI (USA)	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0.03 mg/L Medium: urine

(Cont'd. on page 7)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: February 05, 2018

Revision: February 05, 2018

Trade name: SOLVENT BASE DUCT SEALER - LOW VOC

(Cont'd. of page 6)

	Time: end of shift Parameter: Toluene
	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

· **Exposure controls**

· **General protective and hygienic measures:**

- The usual precautionary measures for handling chemicals should be followed.
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Do not inhale gases / fumes / aerosols.
- Avoid contact with the eyes and skin.
- Pregnant women should strictly avoid inhalation or skin contact.

· **Engineering controls:** Provide adequate ventilation.

· **Breathing equipment:**

- Not required under normal conditions of use.
- Use suitable respiratory protective device in case of insufficient ventilation.
- Use respiratory protection when grinding or cutting material.
- NIOSH or EN approved organic vapor respirator equipped with a dust/mist prefilter should be used.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Eye protection:**



Safety glasses

· **Body protection:** Protective work clothing

· **Limitation and supervision of exposure into the environment**

No relevant information available.

· **Risk management measures** No relevant information available.

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **Appearance:**

- | | |
|--------------------------|-----------------|
| · Form: | Pasty |
| · Color: | Gray |
| · Odor: | Mild |
| · Odor threshold: | Not determined. |

· pH-value:	Not determined.
--------------------	-----------------

(Cont'd. on page 8)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: February 05, 2018

Revision: February 05, 2018

Trade name: SOLVENT BASE DUCT SEALER - LOW VOC

(Cont'd. of page 7)

· Melting point/Melting range:	Not determined.
· Boiling point/Boiling range:	>35 °C (>95 °F)
· Flash point:	<23 °C (<73.4 °F)
· Flammability (solid, gaseous):	Not applicable.
· Auto-ignition temperature:	Not determined.
· Decomposition temperature:	Not determined.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits	
Lower:	Not determined.
Upper:	Not determined.
· Oxidizing properties:	Non-oxidizing.
· Vapor pressure:	Not determined.
· Density:	
Relative density:	Not determined.
Vapor density:	Not determined.
Evaporation rate:	Not determined.
· Solubility in / Miscibility with Water:	Partly miscible.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Other information	No relevant information available.

10 Stability and reactivity

- **Reactivity:** No relevant information available.
- **Chemical stability:**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions**
Flammable.
Used empty containers may contain product gases which form explosive mixtures with air.
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized.
Reacts with reducing agents.
Can react violently with oxygen rich (oxidizing) material. Danger of Explosion.
Forms flammable gases / fumes.
- **Conditions to avoid** Excessive heat.
- **Incompatible materials** Oxidizers
- **Hazardous decomposition products** Carbon monoxide and carbon dioxide

(Cont'd. on page 9)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: February 05, 2018

Revision: February 05, 2018

Trade name: SOLVENT BASE DUCT SEALER - LOW VOC

(Cont'd. of page 8)

11 Toxicological information

· **Information on toxicological effects**

· **Acute toxicity:** Based on available data, the classification criteria are not met.

· **LD/LC50 values that are relevant for classification:**

108-88-3 toluene

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4h	5320 mg/l (mouse)

· **Primary irritant effect:**

· **On the skin:** Based on available data, the classification criteria are not met.

· **On the eye:** Irritating effect.

· **Sensitization:** No sensitizing effects known.

· **IARC (International Agency for Research on Cancer):**

13463-67-7	titanium dioxide	2B
1333-86-4	carbon black	2B

· **NTP (National Toxicology Program):**

None of the ingredients are listed.

· **OSHA-Ca (Occupational Safety & Health Administration):**

None of the ingredients are listed.

· **Probable route(s) of exposure:**

Ingestion.

Eye contact.

Skin contact.

· **Germ cell mutagenicity:** Based on available data, the classification criteria are not met.

· **Carcinogenicity:** Based on available data, the classification criteria are not met.

· **Reproductive toxicity:** Suspected of damaging fertility or the unborn child. Route of exposure: Inhalation.

· **STOT-single exposure:** May cause drowsiness or dizziness.

· **STOT-repeated exposure:** May cause damage to organs through prolonged or repeated exposure.

· **Aspiration hazard:** Based on available data, the classification criteria are not met.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity** No relevant information available.

· **Persistence and degradability** No relevant information available.

· **Bioaccumulative potential:** No relevant information available.

· **Mobility in soil:** No relevant information available.

· **Ecotoxicological effects:**

· **Remark:** Due to mechanical actions of the product (e.g. agglutinations), damages may occur.

· **Additional ecological information**

· **General notes:** Avoid release to the environment.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

(Cont'd. on page 10)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: February 05, 2018

Revision: February 05, 2018

Trade name: SOLVENT BASE DUCT SEALER - LOW VOC




(Cont'd. of page 9)

- **vPvB:** Not applicable.
- **Other adverse effects** No relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.
- **Uncleaned packagings**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

- | | |
|---|---------------------------------------|
| <ul style="list-style-type: none"> · UN-Number · DOT, ADR, IMDG, IATA | <p>UN1133</p> |
| <ul style="list-style-type: none"> · UN proper shipping name · DOT, IATA · ADR, IMDG | <p>Adhesives
ADHESIVES</p> |
| <ul style="list-style-type: none"> · Transport hazard class(es) · DOT | |
| <div style="display: flex; align-items: center;">  <ul style="list-style-type: none"> · Class · Label </div> | <p>3 Flammable liquids
3</p> |
| <ul style="list-style-type: none"> · ADR | |
| <div style="display: flex; align-items: center;">  <ul style="list-style-type: none"> · Class · Label </div> | <p>3 (F1) Flammable liquids
3</p> |
| <ul style="list-style-type: none"> · IMDG, IATA | |
| <div style="display: flex; align-items: center;">  <ul style="list-style-type: none"> · Class </div> | <p>3 Flammable liquids</p> |

(Cont'd. on page 11)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: February 05, 2018

Revision: February 05, 2018

Trade name: SOLVENT BASE DUCT SEALER - LOW VOC

(Cont'd. of page 10)

· Label	3
· Packing group	
· DOT, ADR, IMDG, IATA	II
· Environmental hazards	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	33
· EMS Number:	F-E,S-D

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **DOT**



Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each.

· **ADR**



Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each.

· **IMDG**



Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each.

· **IATA**



Limited Quantity for packages less than 30 kg gross and inner packagings less than 0.5 L each / 1 L net.

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **United States (USA)**
- **SARA**

· **Section 302 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

(Cont'd. on page 12)



Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: February 05, 2018

Revision: February 05, 2018

Trade name: SOLVENT BASE DUCT SEALER - LOW VOC

(Cont'd. of page 11)

Section 313 (Specific toxic chemical listings):

108-88-3 toluene

TSCA (Toxic Substances Control Act)

All ingredients are listed.

Proposition 65 (California)**Chemicals known to cause cancer:**

Reference to chemical component(s) listed below are based on unbound respirable particles and are not generally applicable to product as supplied.

13463-67-7 titanium dioxide

1333-86-4 carbon black

Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

Chemicals known to cause developmental toxicity:

108-88-3 toluene

EPA (Environmental Protection Agency):

67-64-1 acetone

I

108-88-3 toluene

II

IARC (International Agency for Research on Cancer):

13463-67-7 titanium dioxide

2B

1333-86-4 carbon black

2B

NIOSH-Ca (National Institute for Occupational Safety and Health):

13463-67-7 titanium dioxide

1333-86-4 carbon black

Canadian Domestic Substances List (DSL):

All ingredients are listed.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• **Date of preparation / last revision** February 05, 2018 / -

Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bio-accumulable, Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety & Health Administration

(Cont'd. on page 13)



Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: February 05, 2018

Revision: February 05, 2018

Trade name: SOLVENT BASE DUCT SEALER - LOW VOC

(Cont'd. of page 12)

Flam. Liq. 2: Flammable liquids – Category 2
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1

Sources

Website, European Chemicals Agency (echa.europa.eu)
Website, US EPA Substance Registry Services (ofmpub.epa.gov/sorinternet/registry/substreg/home/overview/home.do)
Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)
Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6
Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaassen, Curtis D., ed., ISBN: 978-0-07-176923-5.
Safety Data Sheets, Individual Manufacturers

SDS Prepared by:
ChemTel Inc.
1305 North Florida Avenue
Tampa, Florida USA 33602-2902
Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573
Website: www.chemtelinc.com