



A CSW Industrials Company

SAFETY DATA SHEET

LET'S GO™

Penetrant, lubricant and freeze-up preventer

SECTION 1 - PRODUCT AND COMPANY INFORMATION

Product Name

Lets-Go

Product Codes

73012

Chemical Family

Organic/Inorganic

Use

Cleaner and degreaser

Manufacturer's Name

RectorSeal LLC
2601 Spenwick Drive
Houston, Texas 77055 USA

Date of validation

February 25, 2022

Date of Preparation

February 25, 2022

HMIS Codes

Health 2

Flammability 3

Reactivity 0

PPI B

Emergency Telephone No.

Chemtrec 24 Hours
(800) 424-9300 USA
(703) 527-3887 International

Technical Service Telephone No.

(800) 231-3345 or (713) 263-8001

SECTION 2 - HAZARDS IDENTIFICATION

Emergency Overview

OSHA Hazards

Flammable liquid, Irritant

GHS Classification

Flammable liquids (Category 3)

GHS Label elements, including precautionary statements



GHS02: Flammable

GHS04: Compressed Gas Cylinder

GHS08: Severe Health Hazards

Signal Word: **Danger**

SECTION 2 - HAZARDS IDENTIFICATION

Hazard Statements:

- H226 - Flammable liquid and vapor.
- H304 - May be fatal if swallowed and enters airways.
- H315 - Causes skin irritation.
- H319 - Causes serious eye irritation.
- H280 - Contains gas under pressure; may explode if heated.

Precautionary Statements:

Keep away from heat, sparks, open flames and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place. Avoid breathing mist, vapors and spray.

Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves. If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. Wash contaminated clothing before reuse. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Dispose of contents and container in accordance with local, state and federal regulations.

Summary Of Acute Hazards

Prolonged contact with skin may cause irritation. May cause an allergic skin reaction. Contact with eyes may cause irritation, redness, tearing. Inhalation of mist or vapors may cause respiratory irritation. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Small amounts of liquid aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary edema.

Chronic Health Hazards:

Repeated contact may cause allergic reactions in very susceptible persons. Avoid repeated exposure. Long-term exposure may cause dermatitis. Prolonged inhalation may be harmful.

Note to Physician:

Treatment of overexposure should be directed at the control of symptoms and the clinical condition. If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately. Contains petroleum distillate - vomiting may cause aspiration pneumonia.

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	CAS NUMBER	PERCENT
Distillates (petroleum), hydrotreated light	64742-47-8	70-80%
Propane	74-98-6	5-10%
n-Butane	106-97-8	5-10%
Calcium sulfonates Proprietary		1-5%

Trade Secret Information: A specific chemical identity and/or percentage of composition has been withheld as a trade secret.

SECTION 4 - FIRST AID MEASURES

- IF INHALED:** Move to fresh air. If breathing is difficult, administer oxygen. If not breathing administer artificial respiration or at any sign of loss of consciousness seek immediate medical attention.
- IF ON SKIN:** Remove contaminated clothes. Wash skin thoroughly with soap and water for 15 minutes. Seek medical attention if irritation develops.
- IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
- IF SWALLOWED:** Rinse mouth out with water. Do not induce vomiting unless directed by medical authority. Keep head below hips if vomiting occurs. Seek immediate medical attention. Aspiration hazard. Never give anything by mouth to an unconscious person.

SECTION 5 - FIRE FIGHTING MEASURES

Extinguishing media

Dry chemical, carbon dioxide, foam. Water spray for cooling.

Unsuitable extinguishing media

Water jets or streams.

Special fire fighting procedures

Wear full protective clothing and NIOSH approved SCBA with full facepiece operated in positive pressure or pressure demand. Use water mist to keep material cool in fire situations.

Unusual fire and explosion hazards

FLAMMABLE. Contents under pressure. Exposure to temperatures above 120°F may cause bursting. Keep away from heat, sparks, open flames and other sources of ignition.

Hazardous combustion products

Oxides of carbon.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal Protective Equipment:

Refer to section VIII for proper Personal Protective Equipment.

Spill

Eliminate all sources of ignition. Wear appropriate personal protective equipment. Absorb spill with non-combustible material such as vermiculite, sand or earth. Small releases may be wiped up with wiping material. U.S. regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll-free number for the U.S. Coast Guard National Response Center is 800-424-8802.

Waste Disposal

Dispose of in accordance with local, state and federal regulations. Do not reuse, puncture or incinerate container. Wrap container and place in trash collection.

RCRA Status

Waste likely considered D001 (Ignitable waste), under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).open flames and other sources of ignition.

SECTION 7 - HANDLING AND STORAGE

Handling and storing:

Do not use or store near heat, open flames or other sources of ignition. Wear proper personal protective equipment when using this product. Avoid contact with skin, eyes and clothing. Do not inhale mist or vapor. Use only with adequate ventilation. Do not use or store with strong oxidizers. Protect from sunlight. Store in a well ventilated area. Do not expose to temperatures exceeding 50 °C/122 °F. Pressurized container: Do not pierce or burn, even after use. Store in a cool, dry area.

Other precautions:

Keep out of the reach of children. Aspiration hazard if swallowed. Can enter lungs and cause damage. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Do not taste or swallow. Read and follow the directions on the product label. They are the best guide to using the product in the most effective manner. The label also gives you the necessary safety precautions to protect your health.

Incompatibility:

Strong oxidizing agents.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

HAZARDOUS INGREDIENT	OSHA PEL	ACGIH TLV
Distillates (petroleum), hydrotreated light	Not Established	Not Established
Propane	1000 ppm	1000 ppm
n-Butane	Not Established	1000 ppm
Calcium sulfonates	Not Established	Not Established

ENGINEERING CONTROLS / VENTILATION: Use only outdoors or in a well-ventilated area.

RESPIRATORY PROTECTION: Use only in well-ventilated areas. If exposure levels are exceeded, then organic vapor cartridge respirator or SCBA will be needed.

PERSONAL PROTECTIVE EQUIPMENT: Safety glasses/goggles and chemical resistant gloves.

ADDITIONAL MEASURES: Wear protective clothing to prevent repeated or prolonged contact with product. If clothing becomes contaminated, immediately remove and wash. Wash hands thoroughly after handling.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	Dark gray spray
ODOR:	Mild odor
ODOR THRESHOLD:	N/D
pH:	N/A
MELTING POINT/FREEZING POINT:	N/D
INITIAL BOILING POINT AND BOILING RANGE:	N/D
FLASH POINT:	N/D
EVAPORATION RATE:	N/D
FLAMMABILITY(solid/gas):	Flammable Aerosol
UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS:	75°F (24°C) SETA CC
LOWER FLAMMABILITY LIMIT:	N/D
UPPER FLAMMABILITY LIMIT:	N/D
EXPLOSIVE LIMIT LOWER (%):	N/D
EXPLOSIVE LIMIT UPPER (%):	N/D
VAPOR PRESSURE (mm Hg):	N/D
VAPOR DENSITY (AIR=1):	N/D
RELATIVE DENSITY (H2O=1):	0.90 - 0.95 @ 77 °F (25 °C)
SOLUBILITY(IES):	N/D
PARTITION COEFFICIENT: n-OCTANOL/WATER (KOW):	N/D
AUTOIGNITION TEMPERATURE:	N/D
DECOMPOSITION TEMPERATURE:	N/D
VISCOSITY:	N/D

SECTION 10 - STABILITY AND REACTIVITY

Reactivity: None known.

Chemical Stability: Stable.

Possible hazardous reactions: None known.

Conditions to avoid: Temperatures greater than 122°F and sources of ignition. Avoid incompatibles.

Incompatible materials: Strong oxidizing agents.

Hazardous decomposition products: Oxides of carbon.

SECTION 11 - TOXICOLOGY INFORMATION

Toxicology Data:

Ingredient name

Distillates (petroleum), hydrotreated light (64742-47-8)

Oral-Rat LD50: 5 g/kg

Inhalation-Rat LC50: 2 g/kg

Propane (74-98-6)

Oral-Rat LD50: N/D

Inhalation-Rat LC50: 658 mg/L

n-Butane (106-97-8)

Oral-Rat LD50: N/D

Inhalation-Rat LC50: 30957 mg/m³**Medical Condition Aggravated:** Pre-existing disorders of the skin.**Carcinogenicity:****OSHA:** No**ACGIH:** No**NTP:** No**IARC:** No**OTHER:** N/A

SECTION 12 - ECOLOGICAL INFORMATION

Ecological Data:**Distillates (petroleum), hydrotreated light (64742-47-8)**

LC50 (Daphnia, 48h) > 1000 mg/L

EC50 (Algae, 72h) > 1000 mg/L.

Persistence And Degradability: Component or components of this product are not biodegradable.**Bioaccumulative Potential:** No additional information available.**Mobility In Soil:** This product is mobile in soil.**Other Adverse Effects:** None known.

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste Disposal:

Dispose of in accordance with local, state and federal regulations. Do not reuse, puncture or incinerate container. Wrap container and place in trash collection.

RCRA Status:

Waste likely considered D001 (Ignitable waste), under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION 14 - TRANSPORTATION INFORMATION

PROPER SHIPPING NAME: Aerosols, Ltd. Qty.
 HAZARD CLASS/DIVISION: 2.1
 UN/NA NUMBER: UN1950
 PACKING GROUP: N/A

AIR SHIPMENT

PROPER SHIPPING NAME: Aerosols, flammable.
 HAZARD CLASS/DIVISION: 2.1
 UN/NA NUMBER: UN1950
 PACKING GROUP: N/A

SHIPPING BY WATER:

VESSEL (IMO/IMDG) PROPER SHIPPING NAME: Aerosols.
 HAZARD CLASS/DIVISION: 2.1
 UN/NA NUMBER: UN1950
 PACKING GROUP: N/A
 ENVIRONMENTAL HAZARDS WATER: N/A

SECTION 15 - REGULATORY INFORMATION

TSCA Status:

All chemicals are listed or exempt.

CERCLA (Comprehensive Response Compensation, and Liability Act):

n-Butyl alcohol (71-36-3)	Reportable	Quantity = 5000 pounds
Ethyl benzene (100-41-4)	Reportable	Quantity = 1000 pounds
Naphthalene (91-20-3)	Reportable	Quantity = 100 pounds.

SARA 311/312 Hazard Categories:

Flammable (gases, aerosols, liquids, solids). Gas under pressure. Respiratory or skin sensitization. Aspiration hazard.

SARA 313 Reportable Ingredients:

This product does not contain any chemical components with known CAS numbers that exceed the threshold (de minimis) reporting levels established by SARA Title III, Section 313.

State Regulations:

California Proposition 65: None.

International Regulations: No information available.

Volatile Organic Compounds (VOC): 96%

NFPA Health: 2
NFPA Flammability: 0
NFPA Reactivity: 0
NFPA Other: None

HMIS Health: 2
HMIS Flammability: 0
HMIS Reactivity: 0
HMIS Protection: B

SECTION 16 - OTHER INFORMATION

This document is prepared pursuant to the OSHA Hazard Communication Standard (29 CFR 1910.1200). The information herein is given in good faith, but no warranty, expressed or implied is made. Consult RectorSeal for further information: (713) 263-8001