

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name. : X-PANDO PIPE JOINT COMPOUND

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Sealant for threaded and flanged pipe.

1.3. Details of the supplier of the safety data sheet

X-Pando Products Company
204 Stokes Avenue
Ewing, NJ 08638

1.4. Emergency telephone number

Emergency number : 609-394-0150

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

STOT SE 3 H335
STOT RE 2 H373

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Warning

Hazard statements (GHS-US) :

H335 - May cause respiratory irritation
H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS-US) :

P260 - Do not breathe dust/fume/gas/mist/vapors/spray.
P271 - Use only outdoors or in a well-ventilated area.
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P312 - Call a poison center or doctor if you feel unwell.
P314 - Get medical advice/attention if you feel unwell.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixture

Name	Product identifier	%
Magnesium chloride, hexahydrate	(CAS No.) 7791-18-6	15 - 40
Limestone	(CAS No.) 1317-65-3	15 - 40
Magnesium oxide	(CAS No.) 1309-48-4	10 - 30
Graphite	(CAS No.) 7782-42-5	7 - 13
Dextrin	(CAS No.) 9004-53-9	1 - 5

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Move victim to fresh air and treat symptomatically.

First-aid measures after skin contact : Wash the affected area with soap and water. Seek medical attention if irritation persists.

X-PANDO PIPE JOINT COMPOUND

Safety Data Sheet

- First-aid measures after eye contact : Irrigate eyes with large amounts of water for at least 15 minutes, while holding the eyelid(s) open. Seek medical attention if irritation persists.
- First-aid measures after ingestion : Contact local poison control center or physician IMMEDIATELY.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : May cause irritation to respiratory tract and lung damage if exposure is repeated or prolonged. Although unlikely, inhalation of fumes from heated material may cause metal fume fever, a flu-like illness characterized by delayed symptoms of cough, muscle pains chills and nausea.
- Symptoms/injuries after skin contact : This product may cause skin irritation.
- Symptoms/injuries after eye contact : May cause mechanical irritation if exposed to large amounts of the dust.
- Symptoms/injuries after ingestion : This product may cause gastrointestinal harm and nausea if it is swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.
- Unsuitable extinguishing media : None.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Fire produces oxides of magnesium, calcium and carbon.
- Explosion hazard : None known.

5.3. Advice for firefighters

- Protection during firefighting : Firefighters should wear full fire-fighting turn-out gear (full Bunker gear) including NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Avoid creating or spreading dust.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

None.

6.3. Methods and material for containment and cleaning up

- For containment : If possible, stop flow of product.
- Methods for cleaning up : Vacuum or scoop spilled material and place in closed containers for disposal. Avoid dust generation. Dispose of waste in accordance with local, state and federal regulations.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Avoid generating dust.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store in a closed container in dry area.

7.3. Specific end use(s)

Sealant for threaded and flanged pipe.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Magnesium oxide (1309-48-4)		
USA ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³
Limestone (1317-65-3)		
USA OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³

X-PANDO PIPE JOINT COMPOUND

Safety Data Sheet

Graphite (7782-42-5)		
USA ACGIH	ACGIH TWA (mg/m ³)	2 mg/m ³ (all forms except graphite fibers)
USA OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³ (synthetic)

8.2. Exposure controls

Appropriate engineering controls	: Local exhaust and general ventilation must be adequate to meet exposure standards.
Hand protection	: Wear chemical resistant, impervious gloves for routine industrial use.
Eye protection	: Chemical splash goggles or safety glasses. Emergency eye wash stations and showers should be available within the work area.
Skin and body protection	: An apron or other impermeable body protection is suggested. Full-body chemical protective clothing is recommended for emergency response procedures.
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Powder.
Colour	: Gray to black
Odour	: Odorless
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Self ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 2.56
Solubility	: Water: Appreciable
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

The product is stable at normal handling- and storage conditions.

10.3. Possibility of hazardous reactions

Will not occur.

10.4. Conditions to avoid

Dust generation.

10.5. Incompatible materials

Avoid contact with strong acids and strong bases.

X-PANDO PIPE JOINT COMPOUND

Safety Data Sheet

10.6. Hazardous decomposition products

Hazardous decomposition products such as hydrogen chloride, chlorine and magnesium oxide fumes may develop with exposure to high temperatures.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Magnesium chloride, hexahydrate (7791-18-6)	
LD50 oral rat	8100 mg/kg
ATE (oral)	8100 mg/kg

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Not classified

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : May cause respiratory irritation.

Specific target organ toxicity (repeated exposure) : May cause damage to organs through prolonged or repeated exposure. Prolonged or repeated skin contact may cause burns. Prolonged inhalation of dust may lead to lung damage (pneumoconiosis). Symptoms include coughing, difficulty breathing, and the production of black sputum. Symptoms may be delayed until after years of exposure.

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose of contents/container in accordance with local/regional/national/international regulations.

SECTION 14: Transport information

In accordance with DOT / ADR / RID / ADNR / IMDG / ICAO / IATA

14.1. UN number

Not applicable

14.2. UN proper shipping name

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

Magnesium oxide (1309-48-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Limestone (1317-65-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Graphite (7782-42-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

X-PANDO PIPE JOINT COMPOUND

Safety Data Sheet

Dextrin (9004-53-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

X-PANDO PIPE JOINT COMPOUND

WHMIS Classification Class D Division 2 Subdivision B - Toxic material causing other toxic effects

Magnesium chloride, hexahydrate (7791-18-6)

WHMIS Classification Uncontrolled product according to WHMIS classification criteria

Magnesium oxide (1309-48-4)

Listed on the Canadian DSL (Domestic Substances List) inventory.

WHMIS Classification Uncontrolled product according to WHMIS classification criteria

Limestone (1317-65-3)

WHMIS Classification Class D Division 2 Subdivision A - Very toxic material causing other toxic effects

Graphite (7782-42-5)

Listed on the Canadian DSL (Domestic Substances List) inventory.

WHMIS Classification Class D Division 2 Subdivision A - Very toxic material causing other toxic effects

Dextrin (9004-53-9)

Listed on the Canadian DSL (Domestic Substances List) inventory.

WHMIS Classification Uncontrolled product according to WHMIS classification criteria

15.3. US State regulations

Magnesium oxide (1309-48-4)

U.S. - Massachusetts - Right To Know List
U.S. - Minnesota - Hazardous Substance List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

Limestone (1317-65-3)

U.S. - Massachusetts - Right To Know List
U.S. - Minnesota - Hazardous Substance List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

Graphite (7782-42-5)

U.S. - Massachusetts - Right To Know List
U.S. - Minnesota - Hazardous Substance List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

HMIS III Rating

Health : 1 Slight Hazard - Irritation or minor reversible injury possible
Flammability : 0 Minimal Hazard
Physical : 0 Minimal Hazard

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.